

CRUISER RAMP SPECIFICATIONS

OVERALL WIDTH	Long or Short Bed Trucks = 41 1/8"
OVERALL IN-BED FRAME LENGTH	5'-6" Long Bed = 65" 6'-6" Long Bed = 73.75" 8' Long Bed = 95.5"
SYSTEM WEIGHT	335 Pounds
ELECTRIC WINCH	3000 Pound Capacity W/ 3/16" Heavy Duty Wire Rope Cable
PLATFORM CASTER WHEELS	6"x2" Black Rubber Wheels with wheel grabbers.
MOTORCYCLE WHEEL CHOCK	Locking Wheel Chock. (Ride On-Get Off-Walk Away)
OUTSIDE RAMPS	Length = 95.25" Aluminum Ramps
REAR TIRE RAMP	Length = 94" Aluminum Ramp with a 1500 Pound Weight Capacity
FRONT AXLE TIE-DOWN STRAPS	Ratchet Tie-Down Straps
ACTIVATION SWITCH	Handheld Remote Activation Switch W/ 15 Foot Cable. Allows you to be back with, and watch the motorcycle loading and unloading.
SAFETY CHAINS	Right and Left Front Safety Chains
FRAME FINISH	Black Powder Coat Finish
MOTORCYCLE WEIGHT CAPACITY	1000 Pounds
SHIPPING	Shipped via Truck (Shipped Fully Assembled, Ready to Install) System is shipped on a 4' x 8' pallet. Requires the use of a forklift for truck removal.
PRODUCT LIABILITY INSURANCE	Yes
PATENTED	Yes
SHIPPING	Within 24 hours under most conditions.

eHamilton Enterprises
 4435 First Street, Suite 365
 Livermore, CA 94551
 Ph: 925-215-1762 Ph: 888-510-0678 toll free
 email: jhamilton@ehamiltonenterprises.com